

Axabull®

HYDROEX 4T

4 Stroke Engine Oil (API SL)

Technical Data Sheet

Product Description:

Axabull Hydroex 4T is superior performance engine oil, especially formulated for lubricating all types of 4-stroke engines of two and three wheelers running on Gasoline. It is based on highly refined mineral base oil and proprietary additive system.

Axabull Hydroex 4T meets the following specifications: **API SL & JASO MA2**.

Axabull Hydroex 4T is manufactured based on Axabull's proprietary Torque blend technology.

Torque Blend Technology provides Extra Engine, Clutch & Gear Protection

Features & Benefits:

Axabull Hydroex 4T provides:

- Enhanced engine life and long standing protection of engine components
- Superior engine cleanliness
- Outstanding all weather performance

Applications / Recommendations:

Recommended for all 4 Stroke 2 wheelers manufactured by Hero Moto Corp, Bajaj Auto, TVS, Yamaha, KTM, Mahindra 2 Wheelers, LML, Honda, Suzuki etc. and all imported bikes and engines fitted with catalytic converters.

Typical Properties:

Hydroex 4T	
Properties	Hydroex 4T
SAE Grade	20W-40
Colour	Clear and Bright
Density @ 29.5 °C, gm/ml, ASTM D 1298	0.872
Viscosity, ASTM D 445, cSt @ 40°C	124.1
Viscosity, ASTM D 445, cSt @ 100°C	14.6
Viscosity Index, ASTM D 2270	120
Pour Point, maximum °C, ASTM D 97	-9
Flash Point, minimum°C ASTM D 92	210
TBN, mg KOH/g, ASTM D 2896	7.92
Foam stability seq no I	Nil
Foam stability seq no II	Nil
Foam stability seq no III	Nil

Health and Safety:

Hydroex 4T is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. For MSDS please contact your local Axabull Marketing / Technical Service team.

For Further Information, contact:

AXABULL INDUSTRIES PRIVATE LIMITED

P-3, BLOCK-449/A, Near Aman Hotel.

Baleshwar, NH-8, Palsana, Surat.394317